STEELGREEN MANUFACTURING





FEATURING

O1 Standard Integrated 20/50 Amp Charging System

This powerful charging system gives you the ability to run a high-volume pump, foam markers, and other attachments.

O2 Oil Cooler

Reduces oil temperature, improves lubrication and extends oil change intervals.

O3 Heavy-Duty Shift Solenoid Starter

Designed for long-lasting commercial use.

O4 Dual 30 Gal Spray Tanks

Hold up to 60 gallons of liquid. Plus 75' hose reel comes standard.

O5 High-Density Poly Fertilizer Tray

Two heavy-duty, lightweight trays add 100 lbs of granular product capacity.

O6 22" Rear Wheels

22-inch commercial grade turf tires provide additional hillside stability and faster transport speeds.

O7 Fertilizer Hopper

225-lb hydraulic-driven Spyker® granular system

O8* 21 HP Engine

Vanguard® commercial power 21 HP engine featuring V-Twin OHV Technology, Cooler Cleaner Technology (efficient fan and improved debris management), dynamically balanced crankshaft, and electronic ignition.

Honda® GXV660 21 HP engine is available as a custom option.

O9* Drum Parking Brakes

For brakes that hold (even on hills), our wheel motors have integrated drum brakes on both sides.

10* Overfill Protection

Keeps fluid away from expensive electrical and hydraulic components.

11* Tank Sump with Drain

Completely drain tanks without removing the hose.

12* Easy Access Nozzles

Stainless steel boom with hidden plumbing. Nozzles are easy to reach and change-no special tools required.

13* Donaldson® Air Cleaner

Donaldson® engine air filtration systems offer premium performance and protect and prolong the life of the engine.

14* 3 QT Oil Reservoir

High oil capacity for lower operating temperature.

15* Delavan® Pump

5-chamber positive displacement diaphragm pump with 12 VDC permanent magnet, totally enclosed motor.

Shurflo® diaphragm pump and Hyrpo® high-volume roller pump are also available.

* Pictured on reverse side

FEATURES (CONT'D)



21 HP Engine



Drum Parking Brakes



Overfill Protection



Tank Sump with Drain



Easy Access Nozzles



Donaldson® Air Cleaner



3 QT Oil Reservoir



Delavan® Pump

SPECIFICATIONS

• Spray Capacity: 60 gal

• **Spray Width:** 2' or 6' or 8' or 10'

• Hopper Capacity: 225 lbs

Variable Spread Width: up to 25'

• Fuel Capacity: 5 gal

• Transport Speed: 12 mph

• Rate Production: 240,000 sq. ft. per fill

based on ¼ gallon spray nozzles

DIMENSIONS

Width: 52"

Length: 74"

Height: 54"

Front Tire: 16"

Rear Tire: 22x11.00-10